

GENERAL NOTES

The maximum spacing between channelizing devices in a taper should be 12m; the maximum spacing between channelizing devices used to separate traffic should be 25m.

Traffic safety drums shall be used for channelization devices during nighttime operations. (See Special Provisions)


Channelizing devices shall be a minimum of 0.7m in height.

All signs shall be Black on Orange.

LEGEND

- □ □ CHANNELIZING DEVICES
- ◀ SIGN
- ➡➡ SEQUENTIAL ARROW SIGN

TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES FOR CLOSURE ON A FREEWAY OR EXPRESSWAY.

					REGION NO.	STATE	FED.AID PROJ.NO.	ENVIRONMENTAL AND ENGINEERING SERVICE CENTER	 Washington State Department of Transportation	SR 5 NEWAUKUM RIVER BRIDGE TO THURSTON COUNTY LINE	REFERENCE SHEET NUMBER
DESIGNED BY	B. McMULLEN				10	WASH	IM-0051(236)				
ENTERED BY	W. CASEY										
CHECKED BY	D. HOKANSON										
PROJ. ENGR.	T. PASELK					JOB NUMBER 96X329					SHEET 10 OF 13 SHEETS
DIST. ADM.	G. E. SMITH					CONTRACT NO.					
	DATE	DATE	REVISION	BY					ca\dgn\2738trf.dgn	31 JAN 97	TRAFFIC CONTROL PLAN